



## MTL 802 WXP - PROFESSIONAL WET & DRY



OEM ORIGINAL EQUIPMENT MANUFACTURERS



BUILDING AND CONSTRUCTION



WINE



CLEANING CONTRACTORS



SURFACE PREPARATION



- ✓ Two powerful by-pass motors with independent cooling
- ✓ Compact and mobile
- ✓ PPL filter for chips separation
- ✓ Discharge hose for liquids
- ✓ Accessory kit as standard
- ✓ Submerged pump for the discharge of the liquid
- ✓ Stainless steel AISI304 collection tank
- ✓ Simultaneous operation of liquids vacuuming and discharge

### SUCTION UNIT

Voltage	V - Hz	115 - 60 1~
Power	HP (kW)	2.7 (2)
Max water lift	inH2O (mmH2O)	90.1 (2289)
Max air flow	CFM (m³/h)	211.9 (360)
Suction inlet	in (mm)	2 (50)
Noise level (EN ISO 3744)	dB(A)	76

### FILTER UNIT

Media - Filtration	Polypropylene - 300µm
--------------------	-----------------------

### COLLECTION UNIT

Discharge system	Immersion pump	
Capacity	gal (L)	21 (80)
Discharge speed	gal/min (L/min)	26 (100)

### SIZE

Dimensions	in (cm) WxLxH	21x23x42 (53x59x106)
Weight	lb (kg)	110 (50)



## SUCTION UNIT

The suction is provided by two by-pass motors, using carbon brushes, operated by independent switches and placed inside a sturdy steel casing, filled with soundproofing material.



## FILTER UNIT

A floating device stops the suction whenever the liquid in the container reaches the maximum level and prevents overflowing.



## COLLECTION UNIT

The vacuum cleaner is mounted on a solid steel trolley, provided with a support for hoses when not used, and equipped with oil proof wheels and braking castors.

The stainless steel collection tank has a quick system for the rapid disposal of the material.

The filtered liquid can be discharged easily and quickly thanks to a submersible pump.

## OPTIONALS

- ✓ OTHER VOLTAGES AND FREQUENCIES AVAILABLE UPON REQUEST